



## High density polyethylene wax emulsion

### 【Main Application】

- ★ Water-based ink, water-based paint, water-based paint, water-based varnish
- ★ Leather finishing agent, leveling agent, anti-stick agent
- ★ Textile smoothing agent, softening agent and water resistant finishing
- ★ Flooring, leather, furniture, cars, paper products and other polishing agent
- ★ Paper products lubricant, stripping agent, adhesive, sizing agent Surface organic modification of extinction powder, agriculture and other fields

### 【Specification】

型号 TYPE	外观 APPEARANCE	PH 值 PH VALUE	平均粒径 ( $\mu\text{m}$ ) Particle size	固含量 ( $\pm 1\%$ ) Solid content	乳化体系 Emulsification System	固体蜡熔点 ( $^{\circ}\text{C}$ )Melting pointof solid wax
TL-2011A	Translucent Emulsion	6.0-8.0	$\leq 0.1$	35%	Non/anion	137

### 【Features】

- 1、Extremely high melting point,abrasion resistance,scratch resistance,smooth and good adhesion resistance.
- 2、Good transparency,suitable for high gloss system coating requirements.

### 【 Application 】

- 1.Ideal protector for water-based varnish(metal paint,wood paint,plastic paint),abrasion resistance,scratch resistance,good adhesion resistance,add smoothness and gloss.Similar function in the floor wax and other glazing agent field has also been applied
- 2.Provide abrasion and scratch resistance increase smoothness and gloss,improve feel and polish for leather finishing agent, wax water for shoes,shoe cream
- 3.Textile softener,smoothing agent,increase the wear resistance and tear resistance of the fabric,increase the lubricity of sewing,increase the softness of fabric,and can be used in the printing paste.
- 4.Provide high meting point and good affinity to plastic film in the field of water-based adhesives.
- 5.Paper coating lubricant,stripping agent and sizing agent.
- 6.water-based mold release agent,can be used in metal die casting and other fields.
- 7.Matting powder surface organic modifier,agriculture and other fields.

### 【Attention】

1. close ,cool place,pay attention to antifreeze
2. The original packaging has a shelf life of six months at room temperature.once the container is open, it is recommended to use up within a short period time.

龙口市易久化工科技有限公司依托北京化工大学技术支持,致力于各种蜡乳液和助剂等精细化学品的研发、生产和经营。公司拥有资深的研发团队、先进的生产设备工艺、严格的质保体系和专业的技术服务队伍。多年来各系列产品深得客户好评。  
地址: 山东省龙口市黄城遇家工业园 电话: 0535-8529786 传真: 0535-843088  
技术支持: 13963836616 网址: <http://www.19chem.cn/>  
珠三角地区仓库: 东莞市南城区华博物流中心 C 栋 17/18 档 长三角地区仓库: 江苏省无锡市锡山区东亭镇团结中路 50 号



# 龙口市易久化工科技有限公司

Longkou Excel Chemical Science and Technology Co., Ltd.

诚信打造品牌 科技产生动力 效率迎接挑战

- 
3. To ensure the homogeneity of the product, shake well before use.
  4. when mixing with resins,solvents and other substances,try their applicability in advance,especially with PH values in mind.it is generally recommended to add wax emulsion at the end of the blending process
  5. Only for reference.